



Fire Rated Recessed Floor Hatch

Generated on 03.01.2018

Detailed description

Balanced action internal or external floor access covers, designed to cover a wide range of applications, including patterned tread plate, carpet or vinyl, concrete and walk-on glass. Features gas spring-assisted operation for easy opening. Also available with electric or hydraulic operation.

Features:

- Custom-made to any size.
- Rated up to FACTA Class E vehicle loading.
- Pan-type door recessed from 3–40 mm as standard (100 mm maximum).
- Maximum opening of 85°.
- Gas spring-assisted operation as standard.
- Can accommodate any type of floor infill.
- Hold open stay – prevents accidental closure.

Product guidance - As Standard

Frame:

Patent frame; the access cover is not watertight but is self-draining. Any water passing the seals will be dispersed via an integral drainage channel, which is fitted with an optional internal or external 3/4-inch flexible hose adaptor (for connection to drain by others).

Hinges:

Hidden hinge incorporates an unbroken seal to help prevent the ingress of dirt and moisture.

Product specification

Manufacturer

- Name: Surespan Ltd
- Web: www.surespancovers.com
- Email: sales@surespancovers.com
- Tel: +44 (0)1922 711185
- Fax: +44 (0)1922 497943
- Address: Leamore Close, Leamore Enterprise Park, Walsall, West Midlands WS2 7NL

Product reference HIAC

[Surespan Ltd](#)



Surespan Ltd
Leamore Close
Leamore Enterprise Park
Walsall
West Midlands
WS2 7NL

Tel: +44 (0)1922 711185

www.surespancovers.com
sales@surespancovers.com



Size	600 x 600 mm 750 x 750 mm 900 x 750 mm 900 x 900 mm 1000 x 1000 mm 1200 x 1200 mm 1200 x 1800 mm 1500 x 1500 mm Special order - Insert requirement.
Material	Aluminium Galvanized steel Stainless steel
Infill depth	[_____]
Loading class	Not required FACTA Class A FACTA Class AA FACTA Class AAA FACTA Class B FACTA Class C FACTA Class D FACTA Class E
Fire rating	Not required One hour Two hours Three hours
Sound reduction	25 dB - Standard. 45 dB
Operation	24 V electric motors Gas springs - Standard. Hydraulic
Locking	None CAML Additional cam lock to ensure positive sealing EIM Electrical interlock - Micro-switch. ELB Electronic locking box linked to a BMS system L03 Standard cablock and tee-key L07C Concealed deadlock with cover plate LB Locking padlock box - Provides additional security. PRH Emergency panic-release handle SB Shoot bolt lock - For internal use only.
Accessories	[None] [External flexible hose adaptor] [Glass viewing window] [Internal flexible hose adaptor] [Retractable safety grid] [Retractable ZIP ladder] - To suit floor-to-ceiling height of up to 3.5 m. [Stainless steel cover trim] [SureGrip non-slip finish]



ribproductselector.com

A building products library for construction industry professionals

NBS Plus